

WHAT IS CLAIMED IS:

1. A heater chip for an inkjet printhead, comprising:
 - a substrate;
 - 5 a resistor layer on the substrate having a resistor thickness and a resistor width defining a heater width;
 - a conductor layer on the resistor layer defining a heater length; and
 - an overcoat layer having an overcoat thickness on the resistor layer, the overcoat thickness and the resistor thickness defining a heater thickness wherein
 - 10 the heater length multiplied by the heater width is in a range from about 50 to about 100 micrometers squared and the heater thickness is in a range from about 500 to about 1000 angstroms.

2. A heater chip for an inkjet printhead, comprising:
 - 15 a substrate;
 - a resistor layer on the substrate having a resistor thickness and a resistor width defining a heater width;
 - a conductor layer on the resistor layer defining a heater length; and
 - an overcoat layer having an overcoat thickness on the resistor layer, the
 - 20 overcoat thickness and the resistor thickness defining a heater thickness wherein the heater length multiplied by the heater width is in a range from about 100 to about 150 micrometers squared and the heater thickness is in a range from about 500 to about 1000 angstroms.

- 25 3. A heater chip for an inkjet printhead, comprising:
 - a substrate;
 - a resistor layer on the substrate having a resistor thickness and a resistor width defining a heater width;

a conductor layer on the resistor layer defining a heater length; and
an overcoat layer having an overcoat thickness on the resistor layer, the
overcoat thickness and the resistor thickness defining a heater thickness wherein
the heater length multiplied by the heater width is in a range from about 150 to
5 about 200 micrometers squared and the heater thickness is in a range from about
500 to about 1000 angstroms.

4. A heater chip for an inkjet printhead, comprising:
a substrate;
10 a resistor layer on the substrate having a resistor thickness and a resistor
width defining a heater width;
a conductor layer on the resistor layer defining a heater length; and
an overcoat layer having an overcoat thickness on the resistor layer, the
overcoat thickness and the resistor thickness defining a heater thickness wherein
15 the heater length multiplied by the heater width is in a range from about 200 to
about 250 micrometers squared and the heater thickness is in a range from about
500 to about 1000 angstroms.

5. A heater chip for an inkjet printhead, comprising:
20 a substrate;
a resistor layer on the substrate having a resistor thickness and a resistor
width defining a heater width;
a conductor layer on the resistor layer defining a heater length; and
an overcoat layer having an overcoat thickness on the resistor layer, the
25 overcoat thickness and the resistor thickness defining a heater thickness wherein
the heater length multiplied by the heater width is in a range from about 250 to
about 300 micrometers squared and the heater thickness is in a range from about
500 to about 1000 angstroms.

6. A heater chip for an inkjet printhead, comprising:
- a substrate;
 - a resistor layer on the substrate having a resistor thickness and a resistor
 - 5 width defining a heater width;
 - a conductor layer on the resistor layer defining a heater length; and
 - an overcoat layer having an overcoat thickness on the resistor layer, the
 - overcoat thickness and the resistor thickness defining a heater thickness wherein
 - the heater length multiplied by the heater width is in a range from about 300 to
 - 10 about 350 micrometers squared and the heater thickness is in a range from about
 - 500 to about 1000 angstroms.
7. A heater chip for an inkjet printhead, comprising:
- a substrate;
 - 15 a resistor layer on the substrate having a resistor thickness and a resistor
 - width defining a heater width;
 - a conductor layer on the resistor layer defining a heater length; and
 - an overcoat layer having an overcoat thickness on the resistor layer, the
 - overcoat thickness and the resistor thickness defining a heater thickness wherein
 - 20 the heater length multiplied by the heater width is in a range from about 350 to
 - less than about 400 micrometers squared and the heater thickness is in a range
 - from about 500 to about 1000 angstroms.
8. A heater chip for an inkjet printhead, comprising:
- 25 a substrate;
 - a resistor layer on the substrate having a resistor thickness and a resistor
 - width defining a heater width;
 - a conductor layer on the resistor layer defining a heater length; and

an overcoat layer having an overcoat thickness on the resistor layer, the overcoat thickness and the resistor thickness defining a heater thickness wherein the heater length multiplied by the heater width is in a range from about 50 to about 350 micrometers squared and the heater thickness is in a range from about
5 500 to about 1000 angstroms wherein an energy to emit an ink drop from the heater chip during use is in a range from about 0.007 to about 0.14 microjoules.

9. A heater chip for an inkjet printhead, comprising:

a substrate having a plurality of thin film layers thereon; and
10 a plurality of heaters defined by some of the plurality of thin film layers, at least one of the plurality of heaters having a heater area in a range from about 50 to about 250 micrometers squared and a heater thickness in a range from about 500 to about 6000 angstroms.

15 10. The heater chip of claim 9, wherein an energy to emit a drop of ink from the at least one of the plurality of heaters during use is in a range from about 0.007 to about 0.6 microjoules.

11. A heater chip for an inkjet printhead, comprising:

20 a substrate having a plurality of thin film layers thereon; and
a plurality of heaters defined by some of the plurality of thin film layers, each heater of said plurality of heaters having a heater thickness and heater area wherein the heater area is less than about 250 micrometers squared and the heater thickness is in a range from about 500 to about 6000 angstroms.

25 12. The heater chip of claim 11, wherein an energy to emit a drop of ink from said each heater during use is in a range from about 0.007 to about 0.6 microjoules.

13. The heater chip of claim 11, wherein the plurality of thin film layers include a resistor layer and a conductor layer on the resistor layer.
- 5 14. The heater chip of claim 13, wherein the conductor layer has an anode and a cathode, a distance between the anode and cathode on a surface of the resistor layer defining a heater length of said heater area.
- 15 15. The heater chip of claim 11, wherein the plurality of thin film layers include
10 a resistor layer and an overcoat layer on the resistor layer.
16. The heater chip of claim 15, wherein a thickness of the resistor layer and a thickness of the overcoat layer define said heater thickness.
- 15 17. The heater chip of claim 15, wherein the overcoat layer further includes a passivation layer and a cavitation layer.
18. The heater chip of claim 15, wherein the overcoat layer further includes one of a silicon nitride, a silicon carbide and a diamond like carbon layer.
20
19. The heater chip of claim 11, wherein the plurality of thin film layers include a resistor layer.
20. The heater chip of claim 19, wherein a width of the resistor layer defines a
25 heater width of said heater area.